



DS: 01-11-08
 Subject: BIANCO...
 SAND FILTERS
MODEL: VARIOUS
 Distribution: ALL

PRODUCT PROFILE



Sand Filters

- Improved water flow with the ultra pure filtration.
- Corrosion and U.V. resistant polyester reinforced fibreglass winding design for exceptional strength which will not split.
- Resistance against chemicals and corrosion with the ability to withstand high temperatures.
- Barrel unions for ease of installation and serviceability.
- Top mount heavy duty 7 position including winterize multi-port valve with large easy to operate handle and built in waste port for inspection of backwash water.
- Standard stainless steel long life oil filled pressure gauge.
- Simple backwashing required periodically without need to hose down filter elements.
- Suitable for use with Zeolite filter media.
- Max.Water Temperature: 43°

- 10 YEAR WARRANTY ON TANKS
- 2 YEAR WARRANTY ON COMPONENTS

Model Description

BIA-T21 192 l/m, 300 kPa, 85kg sand
 Barcode: 9312198849011

BIA-T25 270 l/m, 300 kPa, 155kg sand
 Barcode: 9312198849004

BIA-T32 420 l/m, 300 kPa, 210kg sand
 Barcode: 9312198848991

MODEL	Q max (l/min)	Dia (mm)	H (mm)	Ports (mm)	Filter Area (m2)	Sand (kg)	Zelbrite (kg)	6 Hour Turnover (litres)	Max Pressure (kPa)	Max Water Temp (deg C)
BIA-T21	192	525	680	40	0.22	85	65	69120	350	43
BIA-T25	270	625	780	40	0.30	155	120	97200	350	43
BIA-T32	420	800	1035	50	0.50	210	160	151200	350	43



Distributed by **White International Pty Ltd** A.B.N. 48 000 119 380
 52 – 60 Ashford Avenue NSW 2214 PO Box 4755 Milperra BC 1891
 Ph (02) 9783 6000 Fax (02) 9783 6001
SALES HOTLINE 1300 783 601 SALES FAXLINE 02 9783 6003