



DS: 01-10-07  
Subject: BIANCO...  
SUBMERSIBLE PUMP  
**MODEL: BIA-JH40011**  
Distribution: ALL

## **PRODUCT PROFILE**

**BIA-JH40011**



The pump is a light and compact submersible clean water pump supplied wired and ready to install.

The pump has an internal float switch which will not foul and allows for installation in small sumps (min. size 260mm x 160mm x 330mm deep).

When switched to manual mode, the scavenger type base allows pumping down to 5mm.

The pump is characterised by:

- Corrosion resistant pump body and impeller.
- Fully automatic operation.
- Lip type shaft seal.
- 240V single phase TEFC motor with in-built auto reset thermal overload.
- 10m of power cable.
- 12 months warranty.
- Not suitable for construction sites, ponds, fountains or bio-treatment.

### **Liquid:**

Clean water temperature range: 2 – 35 deg C

### **Materials:**

Pump body, Impeller: Technopolymer

Shaft seal and O rings: Nitrile

### **Installation:**

Maximum ambient temperature: 40 deg C

Maximum submergence 8m.

Pipe connections discharge: 1", 1-1/4", 1-1/2"

### **Electrical data:**

Rated voltage: 240V                      Mains frequency: 50 Hz

Rated output 400W

Current: 2 amps

Capacitor: 10 uF

Motor duty: Continuous

Motor type: Asynchronous, TEFC

Motor protection: In-built thermal overload,

Ingress protection: IP 68

Insulation class: F

Power cable length: 10 m H07RNF                      Net weight: 5.0 kg

Dimensions: 220mm L x 330mm H x 160mm W

### **Pump Performance.**

Flows to 125 l/m

Heads to 8m

Maximum particle size 5mm



Distributed by **White International Pty Ltd** A.B.N. 48 000 119 380  
52 – 60 Ashford Avenue NSW 2214 PO Box 4755 Milperra BC 1891  
Ph (02) 9783 6000 Fax (02) 9783 6001  
**SALES HOTLINE 1300 783 601 SALES FAXLINE 02 9783 6003**