DS: 01-10-07
Subject: BIANCO… SUBMERSIBLE PUMP
MODEL: BIA-JH40011
Distribution: ALL

PRODUCT PROFILE

BIA-JH40011

The pump is a light and compact submersible clean water pump supplied wired and ready to install.

The pump has an internal float switch which will not foul and allows for installation in small sumps (min. size 260mm x 160mm x 330mm deep).

When switched to manual mode, the scavenger type base allows pumping down to 5mm.

The pump is characterised by:

- Corrosion resistant pump body and impeller.
- Fully automatic operation.
- Lip type shaft seal.
- 240V single phase TEFC motor with in-built auto reset thermal overload.
- 10m of power cable.
- 12 months warranty.
- Not suitable for construction sites, ponds, fountains or bio-treatment.

Liquid:
Clean water temperature range: 2 – 35 deg C
Materials:
Pump body, Impeller: Technopolymer
Shaft seal and O rings: Nitrile
Installation:
Maximum ambient temperature: 40 deg C
Maximum submergence 8m.
Pipe connections discharge: 1”, 1-1/4”, 1-1/2”
Electrical data:

Rated voltage:	240V	Mains frequency:	50 Hz
Rated output	400W		
Current:	2 amps	Capacitor:	10 uF
Motor duty:	Continuous	Motor type:	Asynchronous, TEFC
Motor protection:	In-built thermal overload,		
Ingress protection:	IP 68	Insulation class:	F
Power cable length:	10 m H07RNF	Net weight:	5.0 kg
Dimensions:	220mm L x 330mm H x 160mm W		

Pump Performance. Flows to 125 l/m
Heads to 8m
Maximum particle size 5mm

Distributed by **White International Pty Ltd** A.B.N. 48 000 119 380
52 – 60 Ashford Avenue NSW 2214 PO Box 4755 Milperra BC 1891
Ph (02) 9783 6000 Fax (02) 9783 6001
SALES HOTLINE 1300 783 601 SALES FAXLINE 02 9783 6003