



DS: 21-06-06
Subject: BIANCO
FIRE PUMP
MODEL: BIA-HP15A
Distribution: ALL

PRODUCT PROFILE



The pump is a compact self-priming engine driven Fire-pump supplied ready to operate complete with hose fittings and suction strainer.

The pump is characterised by:

- Heads to 55 metres
- Flows to 330 litres per minute.
- Suction to 7 metres.
- 1 x 1-1/2", 2 x 1" BSP male discharge ports.
- 1 x 1-1/2" BSP male suction port.
- Roll frame
- Rubber mounting feet
- Low Oil Level Engine Protection.

Liquid:

Clean water temperature range:

2 – 35 deg C

Materials:

Pump body, Diffuser, Impeller:

Aluminium

Mechanical seal:

Carbon/Ceramic/Nitrile

O rings and gaskets:

Nitrile

Installation:

Maximum ambient temperature:

40 deg C

Pipe connections suction/discharge:

1-1/2" BSPM / 1 x 1-1/2", 2 x 1" BSPM

Engine data:

Model:

168F-2

HP:

5.5

Type:

single cylinder, air cooled, 4 stroke

Bore x stroke:

68mm x 54mm

Displacement:

196 cc

Air cleaner:

semi-dry

Ignition:

CDI

Starting:

Recoil

Fuel Capacity:

3.6 litres

Oil Capacity:

1.6 litres


Gross weight:

19.0 kg

Package dimensions:

500mm L x 420mm H x 420mm W

Performance Curves



Distributed by **White International Pty Ltd** A.B.N. 48 000 119 380
52 – 60 Ashford Avenue NSW 2214 PO Box 4755 Milperra BC 1891
Ph (02) 9783 6000 Fax (02) 9783 6001
SALES HOTLINE 1300 783 601 SALES FAXLINE 02 9783 6003