

# BIANCO PUMPZ

DS: 10-07-06  
 Subject: BIANCO...  
 PRESSURE SYSTEM  
**MODEL: BIA-INOX600PC**  
 Distribution: ALL

## PRODUCT PROFILE



The pump is a self-priming pressure system pump supplied wired and ready to install. The self-priming ability provides excellent suction capacity. Used especially for supplying water to domestic installations.

The pump is characterised by:

- Automatic electronic pump control fitted and wired.
- Automatic electronic control provides run dry protection and constant pressure at low flows. Automatic electronic control has in-built check valve.
- Corrosion resistant pump body, diffuser and impeller.
- Mechanical shaft seal.
- 240V single phase TEFC motor with in-built auto reset thermal overload.

**Liquid:**

Clean water temperature range:

2 – 35 deg C

**Materials:**

Pump body, Diffuser, Impeller:

Stainless Steel, Technopolymer

Mechanical seal:

Carbon/Ceramic/Nitrile

O rings:

Nitrile

**Installation:**

Maximum ambient temperature:

40 deg C

Maximum operating pressure

6 bar

Pipe connections suction/discharge:

1" BSP F / 1" BSP M

**Electrical data:**

Rated voltage: 240V

Mains frequency: 50 Hz

Current: 2.6 amps

Capacitor: 20 uF

Motor duty: Continuous

Motor type: Asynchronous, TEFC

Motor protection: In-built thermal overload

Ingress protection: IP 54

Insulation class: F

Power cable length: 1.2 m

Net weight: 9.1 kg

Dimensions: 340mm L x 405mm H x 230mm W

**Pump Performance.**



Distributed by **White International Pty Ltd** A.B.N. 48 000 119 380  
 52 – 60 Ashford Avenue NSW 2214 PO Box 4755 Milperra BC 1891  
 Ph (02) 9783 6000 Fax (02) 9783 6001  
**SALES HOTLINE 1300 783 601 SALES FAXLINE 02 9783 6003**